



JKL PART NUMBER	-A- LENGTH	LCD HIGH OUTPUT WHITE RGB COLOR	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mA rms)	BRIGHTNESS (CANDELA/m ²)	*RATED LIFE (HRS) MINIMUM
BF2661-24B	61±1.0**	9,400°k x = .285 ± .03 y = .283 ± .03	490 @ 0°C	195	5 ± 1	30,000 TYP.	20,000
BF26180-24B	180±3.0		975 @ 0°C	390			
BF26188-24B	188±3.0		1115 @ 0°C	405			
BF26214-24B	214±2.0**		1150 @ 0°C	445			
BF26230-24B	230±3.0		1240 @ 0°C	495			
BF26240-24B	240±3.0		1290 @ 0°C	515			
BF26250-24B	250±1.5		1350 @ 0°C	540			

NOTES:

* RATED LIFE IS DEFINED AS THE POINT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

** LEAD LENGTH 15±3.0.

RATINGS AT 25°C UNLESS OTHERWISE SPECIFIED.

<p>METRIC THIRD ANGLE PROJECTION</p>	<p>DIMENSIONS ARE IN MILLIMETERS</p> <p>TOLERANCE UNLESS OTHERWISE SPECIFIED</p> <p>1 PL +/- REF. 2 PL +/- REF. ANGLE +/- 0</p>	<p>JKL COMPONENTS CORPORATION</p>						
		<p>TITLE MINIATURE COLD CATHODE FLUORESCENT LAMP</p>						
<p>D RATED LIFE HRS MINIMUM & 20,000 - & MARKUP 8/5/09</p> <p>C CORRECT x & y TOLERANCE 7/5/06</p> <p>B LENGTH TOLERANCE CHANGE ON BF26250-24B 2/3/06</p> <p>A ELECTRICAL CHANGES & ADD PART BF2661-24B 10/20/04</p> <p>RELEASED TO CAD MULTI LIST 8/14/03</p>	<p>DRAWN BY L. WENGSTROM</p> <p>APPVD BY L.R.</p> <p>DATE 8/5/09</p>	<p>SIZE A</p> <p>FSCM NO. 55335</p>	<p>DRAWING NO. BF 26-24B</p>	<p>SCALE NONE</p>	<p>RELEASED DATE 8/14/03</p>	<p>REVISION DATE 8/5/09</p>	<p>REV. NO. D</p>	<p>SHEET 1 OF 1</p>
<p>- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED</p>								

REV. NO.	DESCRIPTION/ECO NUMBER	APPVD DATE